

Reference: PL27MZVLIM EAN13: 8057730674300

# **Product title:**

"Color Line" Metal Double Ferrule light bulb sockets - E26

## **Product attributes:**

Finish: Gunmetal, Rust, Kiwi, Sapphire, Lemon

# **Product image:**





#### **Product price:**

\$12.00 tax included

### **Product short description:**

We call these our Color Line double ferrule light sockets because..... you can get them in all types of colors. These double ferrule sockets work with almost all of our pendant light lampshades, including all of our super popular fiber string lampshades and handmade Italian ceramic pendant light shades.

So, why do we call them double ferrule? It's a fancy way of saying two rings. And that's exactly what these light bulb sockets have on them, two rings. The rings are there to hold pendant light shades in place. Most pendant light shade that have an opening between 1 - 5/8 inches to 2 - 5/16 inches wide should work with these double ferrule light bulb sockets.

The ...... comes standard with an included plastic conical strain relief. And if you're looking to some bling to these you can always add a different strain relief by selecting one of our strain relief options found on our website under Lamp Parts and Shades > Accessories > Strain Reliefs. Mix and match a strain relief with the light socket of your choice to make your own unique light bulb socket.

These are e26 base light bulb sockets. That means that they are "standard" base sockets and any light bulb with a normal size base will work with these sockets. That even includes our Giant and XL LED light bulbs.

These light bulb sockets work great with our pendant light cloth covered wire fabric cords.

Be sure to check out our tutorial videos to learn how to wire up these Color Line double ferrule light bulb sockets.

### **Product description:**

Cover: threaded.

Socket: thermosetting polyester T230 (maximum operating temperature).

Rated voltage: 250 Vac.

Rated current: 4 A.

Terminals: screw terminals for rigid or flexible cables from 0.50 to 2.50 mm<sup>2</sup>.

Fixing: with threaded hole M10x1.

Dimensions:

Diameter: 1 - 9/16 inches (40 mm)

Height (without strain relief): 2 - 3/16 inch (55 mm)

Diameter of ferrules: 2 - 5/8 inches (60 mm)



Technical specifications Conical strain relief cable clamp

Height: 1 - 11/16 inch (43 mm) Diameter: 11/32 inch (14.8 mm)

Note that this light bulb socket has a built-in locking safety device that does not allow you to unscrew it once assembled. (This is to protect you from electric shock.)

We ship all our light sockets

not fully assembled and twisted closed

so that the built-in locking safety mechanism is not "locked" when you receive it.

If the safety device does somehow become locked you can unlock this security system, located inside the socket on the side, with a small screwdriver. Please see our tutorial page for videos on how to unlock these light bulb sockets. And If you attempt to unlock the socket you must have the power

#### Disconnected

to the socket before inserting anything into the socket!

#### **Product features:**

Material: Metal Ferrule: Yes Fitting: E26

### **Product gallery:**









